

PRODUCT DATA SHEET

Pri ANCHOR FIX



Pri ANCHOR FIX FOR BARING REBARING

APPLICATION AREA

- Installation of starter bars
- Base plate bolts
- MOT Bolts
- Installation of balustrades



APPLICATION PROCEDURE

- Drill hole $d+2\text{mm}$ or $d+4\text{ mm}$ as per requirement where d =Diameter of bar.
- All bars should be deformed. They should preferably be degreased and all flaky rust removed.
- Mix powder and hardener in given proportion and directly fill in the prepared hole within 15 min.
- Make sure that mix only required quantity because it is rapid hardening agent.

ADVANTAGES

- Easy to mix and apply and rapid strength gain
- Vibration resistant
- Corrosion resistant
- Non-expansive
- Can be placed underwater
- Two grades specifically for vertical and horizontal / overhead use.

TECHNICAL INFORMATION:

Mixed Appearance	Light Green Color Paste
Mixed Density	2100 to 2200 Kg/m ³
Compressive Strength	>75 N/mm ² @ 1 day >95 N/mm ² @ 7 days
Tensile Strength	>18 N/mm ² @ 1 day >23 N/mm ² @ 7 days
Tensile Strength	>45 N/mm ² @ 1 day

PACK SIZE

- 1 kg Set

MFG & MARKETED BY PRIBOND CEMENT PRODUCTS

