PRODUCT DATA SHEET

PRI EPOXY REMOVER



CURED EPOXY RESIDUE REMOVER

PRIBOND'SPRIEpoxy Remover is a powerful, Acid solvent based formula specifically designed for quick and effective removal of cured epoxy residues, such as epoxy grout residues from tiles.

AREAS OF APPLICATION:

• All the types of tile on which epoxy grout has been filled and the spillage of the grout residue remains after the curing.

FEATURES & BENEFITS:

- Solvent based formula
- Designed for quick and effective removal of the grout residue of epoxy over tiles.

METHOD OF APPLICATION:

- 1. Always work in small area, i.e. Less than 0.5 M.
- 2. Apply generously to the area required. Leave to work for approximately 4-5 minutes.
- 3. Once epoxy grout has softened, carefully remove with a suitable tool, i.e. a palette knife.
- 4. Repeat process if necessary to remove all deposits.
- 5. Wash down the area immediately afterwards with detergent and cold water.
- 6. Always dispose of any waste thoroughly

PRECAUTIONS & LIMITATIONS:

- Dangerous to contact with eye, skin & human body.
- It's Damages the alkaline stone & marble. So Please Check before applying.
- Always ensure good ventilation, i.e. open windows and doors.
- Always store in a cool place to opening.
- Protect surrounding areas from damage, i.e. paint work, plastics and textiles.
- Turn off appliances, i.e. gas and electric fires, etc.
- Wear suitable protective clothing

TECHNICAL INFORMATION:

Appearance	Liquid
Colour	Transparent
Odor	Slight OfPetroleum with Acidic
рН	2–3
Spec. Gravity	(20°C): 0.900 Gr. /Cc
Biodegradability	90%
Flashing Point	Not Flammable



COVERAGE:

N.A

PACKING:

Avaliable in 500 ml.

FORTUITOUS LEAKAGE AND WASTE DISPOSAL METHOD:

In case material is released or spilled, clean up most of the product. Store the residue in plastic tanks neutralizes with a solution of hydrochloric acid adjusting the pH to 6-7 then send to water conditioner orcall for a specialized company personal.

