

PRODUCT DATA SHEET

PRiCO NO.3

PRI BOND™

Protection with Perfection

QUICK SETTING AND RAPID HARDENING ADMIXTURE FOR PLAIN CEMENT CONCRETE AND MORTAR

PRiBOND'S PRiCO NO.3 is high versatile free flowing colourless concrete additives in liquid form. It is used as quick setting cum rapid hardening admixture for concrete and plaster. This is also used as Antifreeze/deicing compound for plain concrete in sub-zero climatic conditions.

USES

PRiCO NO.3 is used in underground basement, tunnels, emergency repair and stop huge ingress of water through structures, such as swimming pool, water treatment plant, reservoir etc. is also used for execution of underground waterproofing work which restricts the water ingress for final waterproofing treatment.

It is also used in factory for emergency repair during short duration of shutdown. PRiCO NO.3 is used for pointing of leaky joints.

FEATURES

- Easy to use versatile concrete additives.
- Very useful product for pre-cast industries.
- Very useful emergency repair in factory.
- Highly useful for stoppage of water ingress through underground structures.
- Most useful in cold weather concreting, particularly when temperature
- Reaches below zero degree.
- Very useful for early stripping of shutters.
- Useful for sealing joints in masonry, cracks/joints in tunnels etc.
- For underground waterproofing work plays a very vital role.

APPLICATION

PRiCO NO.3 is diluted with water as recommended above. Before adding the diluted , sand and cement is to be mixed thoroughly in dry condition and then the PRiCO solution is added and mixed thoroughly and quickly so as to avoid stiffening during mixing. For stopping minor leakages and dampness only cement and PRiCO solution are mixed thoroughly to prepare consistency and applied on the surface immediately.

TECHNICAL INFORMATION

Form	Liquid
Colour	Transparent
Dose	1:3 or 4 (PRiCO No.3 : Cement), but may vary depending on site condition
Specific gravity	11.2 ± 0.02
Setting time	Initial – 2 to 3 minutes Final - 4 to 6 minutes

PACKING

1 Kg, 5 Kg & 20 Kg container.

SHELF LIFE

24 months in sealed condition



STORAGE

Keep in a cool dry place and away from direct sunlight

HEALTH & SAFETY PRECAUTIONS

Always use protective gloves and eyewear both during mixing and during application avoid any contact with the eye. If in case happens do not rub, clean with plenty of fresh water immediately.

MFG & MARKETED BY PRIBOND CEMENT PRODUCTS

